



Ruboroc Care Guide




UV POOLS

Cautions

Acids or concentrated muriatic acids will burn the rubber, which will cause a permanent brown or purple appearance that will ruin the aesthetics of the surface

DO NOT "Acid Wash"

Rubaroc.



Cleaning

- ◆ **Use a shopvac or similar vacuum to remove as much dust, dirt and debris as possible. Sweep away larger debris.**
- ◆ **Spray the surface with a hose for lightly soiled areas or use a pressure washer no more than 2500 psi for heavily soiled areas. Keep nozzle at least 12 inches away from rubber surface and set to a light pressure spray (similar for use on vehicle paint).**
- ◆ **You may notice with a newly installed Rubaroc that foam will appear when washing, this is normal and will eventually diminish.**



Stubborn Stains

- ◆ **Use a mild non-biological detergent solution and a clear coloured hard bristle broom, with varying length bristles to remove the stain. (Do not use a wire brush).**
- ◆ **Soak detergent solution on to the Rubaroc surface for two minutes and then rinse away from the pool with clean water.**
- ◆ **Rubbing Alcohol can be used to spot treat stubborn stains such as red-dye stains from wines or soft drinks.**



Algae, Bacteria, Fungi or Mold Growth

Rubaroc will not promote Algae, Bacteria, Fungi or Mold growth, but growth may occur around product due to its porous composition. To prevent and/or clean the Algae, Bacteria, Fungi or Mold in applications where there is standing water or plant life is in abundance and in close proximity to the surface, use a strict regime, every eight weeks, of cleaning with a 10-20% sodium-hypochlorite and water solution (Use LIQUID POOL sodium-hypochlorite, not household chlorine or bleach).



Algae, Bacteria, Fungi or Mold Growth

- ◆ **Apply the chemicals following all safety directions provided, with a pump garden sprayer or watering can.**
- ◆ **Allow solution to soak into the rubber for a maximum of 15 minutes and then rinse the area with a hose or pressure washer up to 2500 psi, directing the water into your pool.**
- ◆ **Remove puddles of water, (uneven surfaces) by sweeping or using a wet/dry vacuum. This will greatly reduce the promotion of any staining as well as Algae, Bacteria, Fungi or Mold buildup.**



Warranty

Rubaroc is warranted for a period of 3 years from the date of installation.

Warranty does not cover normal wear and tear, gloss reduction due to sunlight exposure, slight colour variations from samples or printed brochures, temporary yellowing within the first year, damage due to stains, burns, cuts/gouges, and indentations caused by unusual use, problems caused by moisture, alkali, hydrostatic pressure, cracking, shifting or lifting of the material over which the Rubaroc has been installed.

